

FORTIFIED FOUNDATIONS 5.0mm

REIMAGINED AESTHETICS Experience the timeless aesthetic of Fortified Foundations, our 5.0mm resilient collection. Featuring a selection of woods, stones, abstracts, and textiles in fresh designs and hues, Fortified Foundations allows you to effortlessly specify multiple flooring options for any space. Perfect for healthcare, education, and public spaces, this collection combines proven performance with intentional design. 2 Power Grid in Parchment 5.0 PWG217 and Polished Concrete in Ambient 5.0 POL213. Ashlar and Random Ashlar.

FLEXFORM 5.0mm VALUE-ENGINEER HARD FLOORING

VALUE-ENGINEERED

Art, backed by science.

Milliken's resilient flooring collections create new options for commercial, hospitality, education and retail interiors. Easily coordinate between LVT and Milliken's extensive carpet offerings - designed to work together.

PROGUARD™ REINFORCED POLYURETHANE COATING

Integrated surface technology provides best in class scratch and stain resistance, eliminates the need for additional finishes or harsh chemical treatments.

WEAR LAYER

Heavy commercial grade 22 mil transparent wear layer protects the print visuals and ensures product performs in heavy foot traffic.

PRINTED LAYER

State of the art printing technology providing authentic visuals and designs.

INTEGRAL SOUND ABSORPTION LAYER

Provides improved acoustical performance and supports comfort underfoot.

HIGH PERFORMANCE CORE LAYER

Ensures excellent durability, stability and long term performance.

BACKING LAYER

Engineered balance layer provides stability and durability of the product.





SIBERIAN LARCH

Available in 7" x 48" planks in both 2.5 MM and 5.0 MM.



Haven 5.0 SIB15

Cove 5.0 SIB211







Retreat 5.0 SIB217



Shelter 5.0 SIB48



Harbor 5.0 SIB124

RAW WOOD

Available in 9" x 60" planks.









Revival 5.0 RW69-44



Sandy 5.0 RW219-217



Earthen 5.0 RW206



Light Sandstorm 5.0 RW286



BASSWOOD

Available in 9" x 60" planks.











Vanilla 5.0 BAS204

Honey 5.0 BAS114



Walnut 5.0 BAS10





PIKE

Available in 9" x 60" planks.







Cloud 5.0 PIK144 **Antler** 5.0 PIK124-208



Dew 5.0 PIK121-204

Bark 5.0 PIK176-121



HERITAGE WOOD

Available in $9" \times 60"$ planks.









Honor 5.0 HER218



Pride 5.0 HER208



Courage 5.0 HER76



Legacy 5.0 HER145

SHENENDOAH

Available in 9" x 60" planks.









Mist 5.0 SHE208




Whimsy 5.0 SHE176





Fog 5.0 SHE76-144

Moose 5.0 SHE145



CHEVRON Available in 9" x 60" planks.











Flourish 5.0 CHV144

Thrive 5.0 CHV286





Mesmerize 5.0 CHV15


Abundance 5.0 CHV145





TANGIBLE

Available in 18" x 36" planks.



Dawn 5.0 TAN6









Dusk 5.0 TAN79




POWER GRID







Parchment 5.0 PWG217



Coastal Gray 5.0 PWG180



Hemp 5.0 PWG234



Graphite 5.0 PWG13

TERRAZZO

Available in 18" \times 36" planks in both 2.5 MM and 5.0 MM.



Pearl 5.0 TRZ213



Grit 5.0 TRZ165









Nickel 5.0 TRZ257



Ore 5.0 TRZ13




POLISHED CONCRETE

Available in 36" x 36" tiles.










Ambient 5.0 POL213



Scoring 5.0 POL144



Reflective 5.0 POL180



Sandpaper 5.0 POL13





Milliken™ FOR HUMANKIND.

M/PACT™ Carbon Neutral Product

Climate change is one of the greatest threats facing humanity. That's why our modular flooring products are carbon neutral everywhere in the world. Let's work together for a better tomorrow.

Sustainable features

Milliken LVT is durable resilient flooring engineered with the highest quality raw materials to provide unsurpassed performance and enduring aesthetics. Milliken LVT is 100% orthophthalate free. All production waste is granulated and recycled into backing production to create an internal closed loop recycling process. Milliken LVT is manufactured at facilities that are ISO 9001 compliant.







M/PACT Declare.



FORTIFIED FOUNDATIONS

5.0 M M Product Specs

The information shown here is only a partial listing of the full product information. Visit our website for the complete and most up-to-date specifications of each product.

FLEXFORM™ LVT

Tile Size

7" x 48"

9" x 60"

18" x 18"

18" x 36"

36" x 36"

Construction

High Performance Luxury Vinyl Tile


Finish

ProGuard MAX™ Polyurethane Coating

Wear Layer Thickness 22mil (0.55mm)

Overall Thickness 5.0mm (0.197")

Recommended Installation Methods



Ashlar

Random

Edge Profile Micro Bevel

Critical Radiant Flux (ASTM E648)

Pass - Class 1

Smoke Density (ASTM E662) Pass

Short-Term/Residual Indentation (ASTMF1914-07)

Pass

Flexibility (ASTM F137)

Heat Stability by Color Change (ASTM F1514)

Pass

Light Stability (ASTM F1515)

Pass

Herringbone

(Recommended for 18" x 36" only)

Static Coefficient of Friction (ASTM D2047)

Pass

Dimensional Stability (ASTM F2199)

Pass

Resistance to Chemicals (ASTM F925)

Pass

Static Load Limit (ASTM F970)

Pass

Warranty

22 Year Limited Commercial Wear Warranty










Ashlar

Random

Planks:



Just as texture and physical appearance will vary in samples of wood, beautiful variations of shade are found in this unique LVT product. The shade variation guide reflects our LVT styles ranging from low, to moderate, to high. Low shade variation features soft and subtle gradations. Moderate shade variation contains a more distinguishable variety of hue. And high shade variation models the highest level of contrast. The patterns in **FORTIFIED FOUNDATIONS** have **varying** shade variation as noted throughout the brochure.





SHADE VARIATION GUIDE













FORTIFIED FOUNDATIONS 5.0

FLEXFORM™ LVT

Construction

High Performance Luxury Vinyl Tile

Finish

ProGuard MAX™ Coating

Wear Layer Thickness

22 mil (0.55 mm)

Overall Thickness 5.0 mm (0.197")

Edge Profile

Micro Bevel

InstallationDirect Glue

Nominal Sizes

18" x 18": (457 x 457 mm) 18" x 36": (457 x 914 mm) 36" x 36": (914 x 914 mm) 7" x 48": (192 x 1,219 mm) 9" x 60": (229 x 1,270 mm)

Pieces Per Box

7" x 48": 8

9" x 60": 6

18" x 18": 8

18" x 36": 4

36" x 36": 4

Weight Per Box

7" x 48": 35.31 lb (16.01 kg) 9" x 60": 42.36 lb (19.22 kg) 18" x 18": 34.07 lb (15.45 kg) 18" x 36": 34.27 lb (15.54 kg) 36" x 36": 67.63 lb (30.68 kg)

Quantity Per Box

7" x 48": 18.67 ft² (1.73 m²) 9" x 60": 22.4 ft² (2.08 m²) 18" x 18": 18.0 ft² (1.67 m²) 18" x 36": 18.0 ft² (1.67 m²) 36" x 36": 36.0 ft² (3.34 m²)

Warranties

22 Year Limited Commercial Wear

1 Year Manufacturing Defect Warranty

Recommended Installation Method(s)

Planks:

+ + + + + + + +

SHI AR

† † † † † † † †

+ ↓
↑ →

Tiles:

1 1

1

RANDOM



HERRINGBONE (Recommended for 18" x 36" only)

SUSTAINABLE FEATURES

Milliken LVT is durable resilient flooring engineered with the highest quality raw materials to provide unsurpassed performance and enduring aesthetics.







M/PACT[™]

Declare.

SHOWN ON THE COVER

(Front) Shown in Chevron in Mesmerize 5.0 CHV15. Random. (Back) Shown in Tangible in Dawn 5.0 TAN6. Random Ashlar.

Images in this brochure are approximate for color and pattern scale. Please use actual samples to make your final selections.