THIRD DIMENSION

Wainsford

Broadloom

Construction
Tufted, Textured Frieze

Broadloom Width
13′6″ (4.11 m)

Pattern Repeat
40.5″ x 40.5″

Face Fiber
Milliken Certified WearOn® Nylon

Yarn Finish
Superba® Heatset

Stain Resist / Soil Release
StainSmart®

Dye Method
PrintWorks™ Precision Dyeing

Tufted Face Weight
50 oz/yd² (1,695 g/m²)

Gauge
1/10

Stitches Per Inch
10.5/in (41.3/10 cm)

Finished Pile Height
0.69″ (17.5 mm)

Standard Backing
Endura-Loc™

Nominal Total Thickness
0.82″ (20.8 mm)

Flammability (Radiant Panel ASTM-E-648)
≥ 0.45 (Class I)

Recommended Traffic
Residential

Recommended Maintenance
Capture® Carpet and Fabric Care

Indoor Air Quality—CRI Green Label Plus™
GLP2860, Carpet Category 1Y

LIMITED WARRANTIES – RESIDENTIAL APPLICATIONS
2-Year Latent Manufacturing Defects
Lifetime Abrasive Wear (5 Years on Stairs)
Lifetime Antistatic
Lifetime Stain Resistance - All Food, Beverage, Pet Urine Stains
Lifetime Soil Resistance
Lifetime Texture Retention
See warranty for full details of coverage.

Specifications are subject to normal manufacturing tolerances and may be changed